

Features

- Enclosure frame: Dipcoat- primed, powder-coated
- 19" Rails and metal parts: Dipcoat-primed
- Safety class rating IP20
- Available in heights from 4U up to 12U
- Load capacity 30 kg
- Front door: 4mm impact resistant smoked glass with edge frame
- 210° door opening angle on the front door
- Full height front adjustable galvanized steel 19" profiles
- Roof is prepared for fan units



Color

- RAL 9005 Black
- RAL 7035 Light Grey

Surface finish

- Enclosure frame: Dipcoat- primed, powder-coated.
- 19" Rails and metal parts: Dipcoat-primed
- Rear door and roof: Dipcoat-primed, powder-coated
- Front door: Glass

Material

- Sheet steel

D-SOHO Basic 540x400 LIGHT GREY

CODE	U	COLOR	RAL	HEIGHT (mm)	WIDTH (mm)	DEPTH (mm)	WEIGHT (KG)	LOAD CAPACITY (KG)
DSOB544004UG1	4	GREY	7035	271	540	400	6.8	30
DSOB544006UG1	7	GREY	7035	404	540	400	8.8	30
DSOB544009UG1	9	GREY	7035	493	540	400	10.2	30
DSOB544012UG1	12	GREY	7035	626	540	400	12.8	30

D-SOHO Basic 540x400 BLACK

CODE	U	COLOR	RAL	HEIGHT (mm)	WIDTH (mm)	DEPTH (mm)	WEIGHT (KG)	LOAD CAPACITY (KG)
DSOB544004UB1	4	BLACK	9005	271	540	400	6.8	30
DSOB544006UB1	7	BLACK	9005	404	540	400	8.8	30
DSOB544009UB1	9	BLACK	9005	493	540	400	10.2	30
DSOB544012UB1	12	BLACK	9005	626	540	400	12.8	30