

# Wi-Fi 6 Wireless Mesh Router

WI-AX1800M

## Overview

WI-AX1800M is a gigabit dual-band mesh Wi-Fi 6 wireless router, suitable for large apartments, duplex apartments, villas, small and medium-sized shops, and other scenarios. In addition, multiple routers can be quickly connected without cables or configuration, which solves the configuration challenges of multi-device networking and adding new devices. The router supports the next-generation Wi-Fi 6 standard at 2.4 GHz and 5 GHz. The maximum wireless rate is 574Mbps at 2.4 GHz, the maximum wireless rate is 1201Mbps at 5 GHz, and the concurrent rate can reach 1775Mbps. The recommended number of connected wireless terminals is 100, which is 50% more than that supported by Wi-Fi 5.

## Features

### Powerful Mesh Wi-Fi 6

Ultra-fast Wi-Fi with Mesh Wi-Fi 6 technology, the signal is stronger and the capacity is larger in intensive usage scenarios.

### Ultra-Fast Wi-Fi 6 Speeds

Simultaneous 574 Mbps on 2.4 GHz and 1201 Mbps on 5 GHz totals 1775 Mbps Wi-Fi speeds.

### Fast Roaming

Users can move around the Wi-Fi coverage area without service interruption.

### SD-LAN

Support SD-LAN, provide remote network construction experience between headquarters and branches.

### Cloud Management

The free cloud management platform simplifies a lot of equipment management time and reduces network supervision costs for network administrators.



# Specifications

Products	WI-AX1800M
Version	V2
Hardware Specifications	
Wireless Standards	IEEE 802.11ax/ac wave2/wave1/n/b/g/a
Operating Bands	2.4GHz & 5GHz
Spatial Streams	2.4GHz: 2x2 MIMO 5GHz: 2x2 MIMO
Antenna	2.4GHz: 5dBi ; 5GHz: 5dBi
Signal Rate	Up to 574Mbps at 2.4GHz Up to 1201Mbps at 5GHz
Interface	(3)10/100/1000M Base-T LAN Ethernet ports (1)10/100/1000M Base-T WAN Ethernet port
Power Supply	DC 12V/1A
Power Consumption	<12W
Maximum Transmit Power	<20dbm
Receiver Sensitivity	2.4GHz: 802.11b:-90dBm@11M; 802.11g:-78dBm@54M; 802.11n HT20:-76dBm@MCS7; 802.11n HT40:-72dBm@MCS7; 802.11ax HESU40:-62dBm@MCS11; 5.8GHz: 802.11a:-78dBm@54M; 802.11n VHT40:-65dBm@MCS9; 802.11ac VHT80:-62dBm@MCS9; 802.11ax HESU80:-58dBm@MCS11;
External Buttons	reset button (long press for 8 seconds to restore the factory default configuration)
Dimensions	145mm * 65mm * 166mm
Environment	Operating Temperature: -40°C ~ 55°C Storage Temperature: -40°C ~ 70°C Operating Humidity: 5% ~ 90% (non-condensing) Storage Humidity: 5% ~ 95% (non-condensing)
Software Features	
Operating Mode	Router Mode
Internet Connection Type	Static IP, DHCP, PPPoE Dial-Up
Network Security	Guest Wi-Fi; Hide SSID; Wi-Fi Isolate
	Parental Control; IP/MAC binding
	Wireless Security: WPA-PSK/WPA2-PSK/WPA3-SAE
Advanced Features	Mesh: Supports zero-configuration networking of multiple devices, and supports automatic switching between wired and wireless networking for multiple devices.
	Wi-Fi optimization: Wi-Fi roaming, channel adjustment, power adjustment
	Firewall: Forbid TCP/UDP flood attack
	Application: Port Forwarding; SD-LAN; Open VPN;
	Software upgrade: Firmware upgrade online or Firmware upgradeable via browser
	Diagnostics Utilities: Ping; IPV4 Traceroute; Nslookup
Management and Maintenance	Support local management with web Support remote management with Wi-Tek Cloud platform

# Package Content

Welcome to order our products. After purchasing, you will receive:

Items	Quantity
WI-AX1800M	1 pcs
Network Cable	1 pcs
DC Power	1 pcs
Quick Installation Guide	1 pcs



Wireless-Tek Technology Limited

Address: Biaofang Technology Building 402, Bao'an street,  
Baoan District, Shenzhen City, Guangdong, China

Website: [www.wireless-tek.com](http://www.wireless-tek.com)

Tel: 86-0755-32811290

Email: [sales@wireless-tek.com](mailto:sales@wireless-tek.com)

Technical Support: [tech@wireless-tek.com](mailto:tech@wireless-tek.com)



Technical Support



Cloud Management



Company Website