

Datasheet

Economic 802.3af/at PoE Switch

WI-PS205H | WI-PS210H | WI-PS518GH | WI-PS526GH
 WI-PS305GH | WI-PS308GH | WI-PS309GFH
 WI-PS318GFH | WI-PS326GFH



Overview

Wi-Tek's Economic 802.3af/at PoE Switch Series offers a choice of 4/8/16/24 ports, available in both 100Mbps and 1000Mbps speeds. Break free from PoE distance limitations! Wi-Tek provides a cost-effective PoE solution, empowering your CCTV, Access Point, and other IP-based devices up to 250m away. Most robust features like Extend Mode, PoE Watchdog Function, Port Isolation, provide a lot of value for basic networking needs, creating a versatile and reliable surveillance network to grow your business.

Features

PoE 250m Long Distance to Extend Network

DIP switch provides Extend Mode. All PoE ports can transmit data and power up to 250 meters. No further hardware or configuration is necessary, easy-to-use and cost-saving. Perfect for surveillance camera deployment in large areas.

Smart PoE Watchdog to Reboot Camera Automatically

All PoE ports enable PoE watchdog function, which can detect and reboot the offline compliant PoE powered devices.

Port Isolation to Prevent Broadcast Storm

With VLAN Mode, all PoE ports only can communicate with uplink ports. Avoid data leakage between each port and prevent broadcast storm from disabling network.

Double Uplink to Eliminate the Bandwidth Limit

Uplink ports superficially resembles any other normal port on a switch or hub. Additionally, connecting the uplink port on one switch to the normal port on another switch cab helps expand the size of the network.

DIP – Data Optimization

Default: The transmission distance of PoE port can be up to 100m with 100Mbps.

VLAN: Enable isolation between all downstream ports, while maintaining data communication with the upstream port, effectively preventing broadcast storms.

Extend: Extend the power supply and network transmission distance of PoE ports from the standard 100m to an impressive 250m, though with a reduced port rate of 10Mbps. Elevate your networking experience with enhanced flexibility and efficiency.

CCTV: Extend your network up to 250 meters long distance with VLAN function.

Specifications



| Model | WI-PS205H | WI-PS210H | WI-PS518GH | WI-PS526GH |
|--------------------------------|--|--|---|---|
| Hardware Specifications | | | | |
| Hardware Version | V2 | V1 | V1 | V1 |
| Interfaces | | | | |
| Downlink Ports | 4 * 100Mbps RJ45 PoE Ports | 8 * 100Mbps RJ45 PoE Ports | 16 * 100Mbps RJ45 PoE Ports | 24 * 100Mbps RJ45 PoE Ports |
| Uplink Ports | 2 * 100Mbps RJ45 Ports | 2 * 100Mbps RJ45 Ports | 1 * 1000Mbps RJ45 Port 1 * 1000Mbps Combo Port | 1 * 1000Mbps RJ45 Port 1 * 1000Mbps Combo Port |
| PoE | | | | |
| PoE Port | Port 1 – 4 | Port 1 – 8 | Port 1 – 16 | Port 1 – 24 |
| PoE Standard | 802.3 af/at | | | |
| PoE Power Supply Type | End-span | | | |
| PoE Pin Assignment | 1/2(+), 3/6(-) | | | |
| PoE Power | 30W Max. for each port, 42W Max. for PoE power budget | 30W Max. for each port, 62W Max. for PoE power budget | 30W Max. for each port, 197W Max. for PoE power budget | 30W Max. for each port, 198W Max. for PoE power budget |
| Switch Property | | | | |
| Standards and Protocols | IEEE 802.3, IEEE 802.3u, and IEEE 802.3x | | IEEE 802.3, IEEE 802.3u, and IEEE 802.3x, IEEE 802.3z | |
| Forwarding Mode | Store and Forward | | | |
| Switching Capacity | 1.2 Gbps | 2 Gbps | 7.2 Gbps | 8.8 Gbps |
| Packet Forwarding Rate | 0.89Mpps | 1.49Mpps | 5.36Mpps | 6.55Mpps |
| MAC Address Table | 2k | 2k | 8k | 8k |
| Packet Buffer Memory | 448 K bit | | 4M bit | |
| Jumbo Frame | 1.5 kB | | 10 kB | |
| Power Supply | | | | |
| Input Power | 100–240 V AC 50/60 Hz 1.5A max | 100–240 V AC 50/60 Hz 1.5A max | 100–240 V AC 50/60 Hz 5A max | 100–240 V AC 50/60 Hz 5A max |
| Power Consumption | Idle: 1.83 W 100% Traffic Rate with PoE: 44 W | Idle: 2.41 W 100% Traffic Rate with PoE: 65.7 W | Idle: 7.79 W 100% Traffic Rate with PoE: 205 W | Idle: 8.02 W 100% Traffic Rate with PoE: 206.6 W |



| Model | WI-PS205H | WI-PS210H | WI-PS518GH | WI-PS526GH |
|---------------------------------|--|--|---|--|
| Physical Characteristics | | | | |
| LED Indicators | <p>Power On: The device power on is normal Off: The device is power off or failed</p> <p>PoE On: PoE is working Off: PoE not working</p> <p>DATA Blinking: Data transmission is active and working</p> <p>LNK/ACT On: Data on TX/RX Off: Ports link down</p> | <p>PWR On: The device power on is normal Off: The device is power off or failed</p> <p>PoE On: PoE is working Off: PoE not working</p> <p>DATA Blinking: Data transmission is active and working</p> <p>Max When total PoE output power > Power Budget * 80%, the LED light will be on</p> <p>LNK/ACT On: Data on TX/RX Off: Ports link down</p> | <p>PWR On: The device power on is normal Off: The device is power off or failed</p> <p>PoE On: PoE is working Off: PoE not working</p> <p>DATA Blinking: Data transmission is active and working</p> <p>PoE Max When total PoE output power > Power Budget * 80%, the LED light will be on</p> <p>LNK/ACT On: Data on TX/RX Off: Ports link down</p> <p>18T On: Port 18 link up Off: Port 18 link down</p> <p>17T/17S On: Port 17T/17S link up Off: Port 17T/17S link down</p> | <p>PWR On: The device power on is normal Off: The device is power off or failed</p> <p>PoE On: PoE is working Off: PoE not working</p> <p>DATA Blinking: Data transmission is active and working</p> <p>PoE Max When total PoE output power > Power Budget * 80%, the LED light will be on</p> <p>LNK/ACT On: Data on TX/RX Off: Ports link down</p> <p>25T On: Port 25 link up Off: Port 25 link down</p> <p>26T/26S On: Port 26T/26S link up Off: Port 26T/26S link down</p> |
| Fan Quantity | Fanless | | 1 | |
| Dimensions (W*D*H) | 140x82x28 mm | 167x99x33 mm | 281x188x44 mm | 281x188x44 mm |
| Weight | Net Weight: 0.32 kg | Net Weight: 0.47 kg | Net Weight: 1.75 kg | Net Weight: 1.82 kg |
| | Package Weight: 0.60 kg | Package Weight: 0.77 kg | Package Weight: 2.37 kg | Package Weight: 2.45 kg |
| Installation | Desktop | | Desktop、 Rack-mount | |
| Button | | | | |
| DIP Switch | Default/CCTV (CCTV=250m Extend mode + VLAN mode) | Default/CCTV (CCTV=250m Extend mode + VLAN mode) | Default/VLAN/CCTV (CCTV=250m Extend mode + VLAN mode) | Default/VLAN/Extend (CCTV=250m Extend mode + VLAN mode) |



| Model | | WI-PS205H | WI-PS210H | WI-PS518GH | WI-PS526GH |
|-----------------------|----------------|--|-----------|--|------------|
| Environmental | | | | | |
| Reliability | Surge Immunity | EC 61000-4-5 Common mode ±4kV Differential mode ±2kV | | | |
| | ESD Protection | IEC 61000-4-2 Contact discharge ±6kV Air discharge ± 8kV | | | |
| Operating Temperature | | -10°C to 55°C(14°F to 131°F) | | | |
| Operating Humidity | | 10%-90% RH no condensation | | | |
| Storage Temperature | | -40°C to 70°C(-40°F to 158°F) | | | |
| Storage Humidity | | 5%-90% RH no condensation | | | |
| Others | | | | | |
| Certification | | CE, FCC, RoHS, UKCA, RCM | | | |
| Network Media | | 10Base-T: Pair 2 Category 3 (cat 3) and above UTP/ STP(≤100m) 100Base-TX: Pair 2 Category 5 (cat 5) and above UTP/ STP(≤100m) | | 10Base-T: Pair 2 Category 3 (cat 3) and above UTP/ STP(≤100m) 100Base-TX: Pair 2 Category 5 (cat 5) and above UTP/ STP(≤100m) 1000BASE-TX: 6 Category and above UTP(≤100m) | |





| Model | WI-PS305GH | WI-PS308GH | WI-PS309GFH | WI-PS318GFH | WI-PS326GFH |
|--------------------------------|---|---|---|--|--|
| Hardware Specifications | | | | | |
| Hardware Version | V1 | V2 | V1 | V1 | V1 |
| Interfaces | | | | | |
| Downlink Ports | 4 1000Mbps RJ45 PoE Ports | 8 1000Mbps RJ45 PoE Ports | 8 1000Mbps RJ45 PoE Ports | 16 1000Mbps RJ45 PoE Ports | 24 1000Mbps RJ45 PoE Ports |
| Uplink Ports | 1 1000Mbps RJ45 Port | 2 1000Mbps RJ45 Ports | 1 1000Mbps RJ45 Ports 1 1000Mbps SFP Port | 2 1000Mbps Combo Ports | 2 1000Mbps SFP Slots |
| PoE | | | | | |
| PoE Port | Port 1– 4 | Port 1– 8 | Port 1– 8 | Port 1– 16 | Port 1– 24 |
| PoE Standard | 802.3 af/at | | | | |
| PoE Power Supply Type | End-span | | | | |
| PoE Pin Assignment | 1/2(+), 3/6(-) | | | | |
| PoE Power | 30W Max. for each port, 57W Max. for PoE power budget | 30W Max. for each port, 62W Max. for PoE power budget | 30W Max. for each port, 64W Max. for PoE power budget | 30W Max. for each port, 197W Max. for PoE power budget | 30W Max. for each port, 252W Max. for PoE power budget |
| Switch Property | | | | | |
| Standards and Protocols | IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3ab, and IEEE 802.3z | | | | |
| Forwarding Mode | Store and Forward | | | | |
| Switching Capacity | 10 Gbps | 20 Gbps | 20 Gbps | 36 Gbps | 52 Gbps |
| Packet Forwarding Rate | 7.44 Mpps | 14.88 Mpps | 14.88 Mpps | 26.78 Mpps | 38.69 Mpps |
| MAC Address Table | 2k | 4k | | | 8k |
| Packet Buffer Memory | 1 Mbit | 2 Mbit | 1.5 Mbit | 4.1 Mbit | 4.1 Mbit |
| Jumbo Frame | 10 kB | | | | |
| Power Supply | | | | | |
| Input Power | 100–240 V AC 50/60 Hz 1.5A max | | | 100–240 V AC 50/60 Hz 5A max | 100–240 V AC 50/60 Hz 5A max |
| Power Consumption | Idle: 2.38 W 100% Traffic Rate with PoE: 59.4 W | Idle: 3.32 W 100% Traffic Rate with PoE: 65.6 W | Idle: 3.13 W 100% Traffic Rate with PoE: 67.8 W | Idle: 10.3 W 100% Traffic Rate with PoE: 207.3 W | Idle: 21.1 W 100% Traffic Rate with PoE: 273.5 W |



| Model | WI-PS305GH | WI-PS308GH | WI-PS309GFH | WI-PS318GFH | WI-PS326GFH |
|---------------------------------|--|--|--|--|--|
| Physical Characteristics | | | | | |
| LED Indicators | <p>Power On: The device power on is normal Off: The device is power off or failed</p> <p>PoE On: PoE is working Off: PoE not working</p> <p>DATA Blinking: Data transmission is active and working</p> <p>LNK/ACT On: Data on TX/RX Off: Ports link down</p> | <p>PWR On: The device power on is normal Off: The device is power off or failed</p> <p>PoE On: PoE is working Off: PoE not working</p> <p>DATA Blinking: Data transmission is active and working</p> <p>LNK/ACT On: Data on TX/RX Off: Ports link down</p> | <p>Power On: The device power on is normal Off: The device is power off or failed</p> <p>PoE On: PoE is working Off: PoE not working</p> <p>DATA Blinking: Data transmission is active and working</p> <p>LNK/ACT On: Data on TX/RX Off: Ports link down</p> | <p>PWR On: The device power on is normal Off: The device is power off or failed</p> <p>PoE On: PoE is working Off: PoE not working</p> <p>DATA Blinking: Data transmission is active and working</p> <p>PoE Max When total PoE output power > Power Budget * 80%, the LED light will be ON</p> <p>LNK/ACT On: Data on TX/RX Off: Ports link down</p> | <p>PWR On: The device power on is normal Off: The device is power off or failed</p> <p>PoE On: PoE is working Off: PoE not working</p> <p>DATA Blinking: Data transmission is active and working</p> <p>PoE Max When total PoE output power > Power Budget * 80%, the LED light will be ON</p> <p>LNK/ACT On: Data on TX/RX Off: Ports link down</p> |
| Fan Quantity | Fanless | | | 1 | 2 |
| Dimensions (W*D*H) | 140x82x28 mm | 168x99x33 mm | 168x99x33 mm | 281x185x44 mm | 442x213x44 mm |
| Weight | Net Weight: 0.36 kg | Net Weight: 0.52 kg | Net Weight: 0.51 kg | Net Weight: 1.84 kg | Net Weight: 2.47 kg |
| | Package Weight: 0.64 kg | Package Weight: 0.81 kg | Package Weight: 0.82 kg | Package Weight: 2.48 kg | Package Weight: 3.27 kg |
| Installation | Desktop | | | Desktop、 Rack-mount | |
| Button | | | | | |
| DIP Switch | Default/CCTV(CCTV=250m Extend mode + VLAN mode) | | | | |
| Environmental | | | | | |
| Reliability | Surge Immunity | EC 61000-4-5 Common mode ±4kV Differential mode ±2kV | | | |
| | ESD Protection | IEC 61000-4-2 Contact discharge ±6kV Air discharge ± 8kV | | | |
| Operating Temperature | -10°C to 55°C(14°F to 131°F) | | | | |
| Operating Humidity | 10%~90% RH no condensation | | | | |
| Storage Temperature | -40°C to 70°C(-40°F to 158°F) | | | | |
| Storage Humidity | 5%~90% RH no condensation | | | | |




| Model | WI-PS305GH | WI-PS308GH | WI-PS309GFH | WI-PS318GFH | WI-PS326GFH |
|---------------|--|------------|-------------|-------------|-------------|
| Others | | | | | |
| Certification | CE, FCC, RoHS, UKCA, RCM | | | | |
| Network Media | 10Base-T: Pair 2 Category 3 (cat 3) and above UTP/ STP(≤100m) 100Base-TX: Pair 2 Category 5 (cat 5) and above UTP/ STP(≤100m) 1000BASE-TX: 6 Category and above UTP(≤100m) | | | | |



Appearances and Dimensions


WI-PS205H

Dimensions (mm)




Front Panel

Rear Panel




WI-PS210H


Dimensions (mm)



Front Panel




Rear Panel




WI-PS518GH


Dimensions (mm)



Front Panel




Rear Panel




WI-PS526GH


Dimensions (mm)



Front Panel




Rear Panel




WI-PS305GH


Dimensions (mm)



Front Panel




Rear Panel




WI-PS308GH


Dimensions (mm)



Front Panel




Rear Panel




WI-PS309GFH


Dimensions (mm)



Front Panel




Rear Panel




WI-PS318GFH


Dimensions (mm)



Front Panel




Rear Panel




WI-PS326GFH


Dimensions (mm)



Front Panel



Rear Panel



Package Contents

Welcome to order our products. After purchasing, you will receive:

| WI-PS205H WI-PS305GH | |
|---|----------|
| Items | Quantity |
| Switch | 1 pcs |
| AC Power Cord | 1 pcs |
| Quick Installation Guide | 1 pcs |
| WI-PS210H WI-PS308GH WI-PS309GFH | |
| Items | Quantity |
| Switch | 1 pcs |
| AC Power Cord | 1 pcs |
| Quick Installation Guide | 1 pcs |
| Mats | 4 pcs |
| WI-PS518GH WI-PS526GH WI-PS318GFH WI-PS326GFH | |
| Items | Quantity |
| Switch | 1 pcs |
| AC Power Cord | 1 pcs |
| Rack Mount kit (Hooks × 2; Mats × 4; Screws × 8) | 1 pcs |
| Quick Installation Guide | 1 pcs |



Wireless-Tek Technology Limited

Address: Biaofan Technology Building 402, Bao'an street,
Baoan District, Shenzhen City, Guangdong, China

Website: www.wireless-tek.com

Tel: 86-0755-32811290

Email: sales@wireless-tek.com

Technical Support: tech@wireless-tek.com



Technical Support



Cloud Management



Company Website