

DATA SHEET

POWER REX Ø 3 mm - fiberglass rod with box



CONTENT





1 x box, 1 x fiberglass rod Ø 3 mm with 2 pressed ending joint Ø 7 mm,
1 x RUNPOGLIDER, 1 x pulling grip, 1 x cable pulling grip Ø 6–9 mm with swivel,
1 x spezial glue 3 g, 3 x coupling joint Ø 7 mm,
5 x ending joint Ø 7 mm, 2 x eyelet Ø 7 mm
All accessories are equipped with stainless steel RUNPOTEC RTG Ø 6 mm thread.

SPECIFICATION

(RRP/excl. of VAT)

LENGTH	20 m	30 m	40 m	50 m		
WEIGHT/KG	1,12 kg	1,24 kg	1,34 kg	1,46 kg		
ITEM NO.	10087	10088	10089	10090		
PRICE €	€ 86,00	€ 98,00	€ 108,00	€ 119,90		
ROD MATERIAL	fiberglass core with PP sheath					

Recommended tube diameter, bending radius and tension loads of POWER REX Ø 3 mm

Ø				
3 mm	16–50 mm	55 mm	450 Kg	120 Kg

DESCRIPTION

POWER REX cable installation system with glassfiber rod + complete repair set in a practicable box. RUNPOTEC POWER REX is a further development of the 3 mm glassfiber rod - technical advance due its patented RUNPOGLIDER with swivel, better gliding quality, higher pulling force, a bigger eyelet, no more need for changing the heads. Optimal for pipe conduit diameter 16–50 and all pipes with already installed cables. Ending joint with RUNPOTEC RTG Ø 6 mm thread.